

## Fiber splice panel 24 x SC/LCD 1U (unloaded)

### FO Panel sliding 24 x LC Duplex/SC Simplex cut out, unloaded, 1U, black

Unloaded Fiber Splice Panel is a hardware unit designed to organize, protect, and terminate fiber optic cables by fusion-splicing incoming fibers to internal pigtails connected to fiber optic adapters on front side of panel.

- Sliding drawer with 4 cable entry
- 24 or 48 cutouts for SC simplex/LC duplex, SC duplex/LC quad adapters
- 1HU and 2HU
- Adapters, Pigtails, Splice trays and SMOUVs must be ordered separately



#### SPECIFICATION

Hardware Type	Splicing Panel with Sliding Drawer
Number of Rack Spaces	1U
Weight	3,7 kg (empty panel)
Port Cutouts	24 x SC/LCD
Loaded Ports Count	Empty
Port Fiber Mode	not applicable
Cable Entries	Cable Glands PG-13.5 (4 pcs)
Loaded	Empty
Material	Aluminum, steel
Colour	Black
Dimensions WxHxD	442 x 44 x 277 mm
Operating Temperature	-10 to 50°C
Storage Temperature	-20 to 60°C

#### Part Numbers

C1120000	FO Panel sliding 24 x LC Duplex/SC Simplex cut out, unloaded, 1U, black
----------	---