

Fiber splice panel 48 x SCD/LCQ 2U (unloaded)

FO Panel sliding 48 x SC Duplex/LC Quad cut out, unloaded, 2U, black

Unloaded Fiber Splice Panel is a hardware unit designed to organize, protect, and terminate fiber optic cables by fusion-splicing incoming fibers to internal pigtails connected to fiber optic adapters on front side of panel.

- Sliding drawer with 4 cable entry
- 24 or 48 cutouts for SC simplex/LC duplex, SC duplex/LC quad adapters
- 1HU and 2HU
- Adapters, Pigtails, Splice trays and SMOUVs must be ordered separately



SPECIFICATION

Hardware Type	Splicing Panel with Sliding Drawer
Number of Rack Spaces	2U
Weight	4,8 kg (empty panel)
Port Cutouts	48 x SCD/LCQ
Loaded Ports Count	Empty
Port Fiber Mode	not applicable
Cable Entries	Cable Glands PG-13.5 (8 pcs)
Loaded	Empty
Material	Aluminum, steel
Colour	Black
Dimensions WxHxD	442 x 90 x 369 mm
Operating Temperature	-10 to 50°C
Storage Temperature	-20 to 60°C

Part Numbers

C1260000	FO Panel sliding 48 x SC Duplex/LC Quad cut out, unloaded, 2U, black
----------	--