

Fiber splice panel 12 x LCD OM4 1U (loaded)

FO Panel sliding 12 x LC Duplex ports, 50/125 OM4, loaded, 1U, black

Loaded Fiber Splice Panel is a hardware unit designed to organize, protect, and terminate fiber optic cables by fusion-splicing incoming fibers to internal pigtails connected to fiber optic adapters on front side of panel.

- Sliding drawer with 4 cable entry
- Versions for 6|12|24|48 SC simplex, LC duplex, SC duplex, LC quad OM3|OM4|SM-UPC|SM-APC adapters
- 1HU and 2HU
- Adapters, Pigtails, Splice trays and SMOUVs are included



SPECIFICATION

Hardware Type	Splicing Panel with Sliding Drawer
Number of Rack Spaces	1U
Weight	3,7 kg (empty panel)
Port Cutouts	24 x SC/LCD
Loaded Ports Count	12 ports
Port Fiber Mode	OM4
Cable Entries	Cable Glands PG-13.5 (4 pcs)
Loaded	Adapters - 12 pcs, Pigtails - 24 pcs, Splice Tray(s) - 1 pcs, SMOUV splice protectors - 24 pcs
Material	Aluminum, steel
Colour	Black
Dimensions WxHxD	442 x 44 x 277 mm
Operating Temperature	-10 to 50°C
Storage Temperature	-20 to 60°C

Part Numbers

C1122B10	FO Panel sliding 12 x LC Duplex ports, 50/125 OM4, loaded, 1U, black
----------	--