

Fiber splice panel 12 x SC-UPC SM 1U (loaded)

FO Panel sliding 12 x SC-UPC Simplex ports, 09/125 OS2, loaded, 1U, black

Loaded Fiber Splice Panel is a hardware unit designed to organize, protect, and terminate fiber optic cables by fusion-splicing incoming fibers to internal pigtails connected to fiber optic adapters on front side of panel.

- Sliding drawer with 4 cable entry
- Versions for 6|12|24|48 SC simplex, LC duplex, SC duplex, LC quad OM3|OM4|SM-UPC|SM-APC adapters
- 1HU and 2HU
- Adapters, Pigtails, Splice trays and SMOUVs are included



SPECIFICATION

| | |
|-----------------------|--|
| Hardware Type | Splicing Panel with Sliding Drawer |
| Number of Rack Spaces | 1U |
| Weight | 3,7 kg (empty panel) |
| Port Cutouts | 24 x SC/LCD |
| Loaded Ports Count | 12 ports |
| Port Fiber Mode | SM UPC |
| Cable Entries | Cable Glands PG-13.5 (4 pcs) |
| Loaded | Adapters - 12 pcs, Pigtails - 12 pcs, Splice Tray(s) - 1 pcs, SMOUV splice protectors - 12 pcs |
| Material | Aluminum, steel |
| Colour | Black |
| Dimensions WxHxD | 442 x 44 x 277 mm |
| Operating Temperature | -10 to 50°C |
| Storage Temperature | -20 to 60°C |

Part Numbers

| | |
|----------|---|
| C1122310 | FO Panel sliding 12 x SC-UPC Simplex ports, 09/125 OS2, loaded, 1U, black |
|----------|---|