

## Fiber splice panel 48 x SC-APC SM 2U (loaded)

FO Panel sliding 48 x SC-APC Simplex ports, 09/125 OS2, loaded, 2U, black

Loaded Fiber Splice Panel is a hardware unit designed to organize, protect, and terminate fiber optic cables by fusion-splicing incoming fibers to internal pigtails connected to fiber optic adapters on front side of panel.

- Sliding drawer with 4 cable entry
- Versions for 6|12|24|48 SC simplex, LC duplex, SC duplex, LC quad OM3|OM4|SM-UPC|SM-APC adapters
- 1HU and 2HU
- Adapters, Pigtails, Splice trays and SMOUVs are included



### SPECIFICATION

|                       |  |
|-----------------------|--|
| Hardware Type         | Splicing Panel with Sliding Drawer   |
| Number of Rack Spaces | 2U   |
| Weight                | 4,8 kg (empty panel)   |
| Port Cutouts          | 48 x SC/LCD  |
| Loaded Ports Count    | 48 ports   |
| Port Fiber Mode       | SM APC   |
| Cable Entries         | Cable Glands PG-13.5 (8 pcs)   |
| Loaded                | Adapters - 48 pcs, Pigtails - 48 pcs, Splice Tray(s) - 2 pcs, SMOUV splice protectors - 48 pcs |
| Material              | Aluminum, steel  |
| Colour                | Black  |
| Dimensions WxHxD      | 442 x 90 x 369 mm  |
| Operating Temperature | -10 to 50°C  |
| Storage Temperature   | -20 to 60°C  |

### Part Numbers

|          |   |
|----------|---|
| C1255410 | FO Panel sliding 48 x SC-APC Simplex ports, 09/125 OS2, loaded, 2U, black |
|----------|---|